

Material Safety data sheet for AIREX® T90 T92

According to Regulation (EC) No. 1907/2006

Page 1 of 3

revised: 25.01.2011

1.	<p>Identification of substance / preparation and of the company</p> <p>AIREX® T90/T92 Rigid foam (T90.100, T90.150, T90.210) (T92.100, T92.110, T92.130, T92.200)</p> <p><i>Use of substance / preparation :</i> Core material in sandwich constructions</p> <p><i>Company identification:</i> Airex AG 5643 Sins, Switzerland Tel +41 41 789 66 00 Fax +41 41 789 66 60</p>
2.	<p>Hazards identification</p> <p>AIREX® T90/T92 does not constitute any risk to public health and environment if it is used as intended.</p> <p>Fine dust is produced while sawing, milling, grinding and sanding.</p> <p>Molten product adheres to the skin and causes burns.</p>
3.	<p>Composition / Information on ingredients</p> <p>Rigid polymeric foam on the basis of Polyethylenterephthalate.</p> <p><i>Blowing agent:</i> Carbon dioxide (CO₂)</p>
4.	<p>First aid measures</p> <p><i>Inhalation of gases in case of fire:</i> Move victim to fresh air and obtain medical attention.</p> <p><i>Skin contact:</i> Molten product on the skin should be cooled rapidly with cold water, but not pulled off. Obtain medical attention.</p> <p><i>Eye contact:</i> Flush with water if irritation develops.</p> <p><i>Ingestion:</i> No special measures required. Seek medical attention if symptoms develop.</p>
5.	<p>Fire-fighting measures</p> <p><i>Specific hazards:</i> Not classified as flammable but will burn. Toxic gases contain carbon monoxide (CO) and others.</p> <p><i>Suitable extinguishing media:</i> Foam, water spray, extinguishing powder, carbon dioxide.</p> <p><i>Extinguishing media which must not be used:</i> direct water jet.</p> <p>Use respiratory protection independent of recirculated air.</p>
6.	<p>Accidental release measures</p> <p>No special measures required.</p>
7.	<p>Handling and storage</p> <p><i>Handling:</i> No special measures required. Avoid generation or accumulation of dusts. Take precautionary measures against static discharges. Earth all equipment.</p> <p><i>Storage:</i> Stow away from immediate and dangerous sources of ignition. Danger of electrostatic charges when stored in very dry areas.</p>

3A COMPOSITES CORE MATERIALS
www.corematerials.3AComposites.com



Europe / Middle East / Africa:
 Airex AG
 Industrie Nord 26
 5643 Sins, Switzerland
 Tel +41 41 789 66 00
 Fax +41 41 789 66 60
corematerials@3AComposites.com

North America / South America:
 Baltek Inc.
 108 Fairway Court
 Northvale, NJ 07647, USA
 Tel +1 201 767 14 00
 Fax +1 201 387 66 31
corematerials.americas@3AComposites.com

Asia / Australia / New Zealand:
 3A Composites (China) Ltd.
 Shangfeng Road 933, Building 6, Pudong
 201201 Shanghai, China
 Tel +86 21 585 86 006
 Fax +86 21 338 272 98
corematerials.asia@3AComposites.com

Material Safety data sheet for AIREX® T90 T92

According to Regulation (EC) No. 1907/2006

Page 2 of 3

revised: 25.01.2011

8.	<p>Exposure control / personal protection</p> <p><i>Exposure limit values:</i> Not applicable.</p> <p><i>Exposure controls:</i> The use of gloves, protective goggles and dust masks and also the use of dust extraction equipment is recommended for sawing, milling, grinding and sanding. For thermoforming, the workplace should be continuously supplied with fresh air. Where necessary, a respiratory protection is recommended.</p>
9.	<p>Physical and chemical properties</p> <p><i>Physical state / form:</i> Polymer foam sheet with visible cell structure.</p> <p><i>Colour:</i> White</p> <p><i>Melting temperature:</i> 250 °C</p> <p><i>Decomposition temperature</i> > 340 °C</p> <p><i>Flash ignition temperature</i> 370 °C DIN 51794</p> <p><i>Density:</i> 100 – 240 kg/m³ ISO 845</p> <p><i>Solubility: Insoluble in:</i> Water, sea water, acids, alkalis, aliphatic hydrocarbons</p> <p><i>Soluble in:</i> Aromatic hydrocarbons, ketones, chlorinated hydrocarbons</p>
10.	<p>Stability and reactivity</p> <p><i>General information:</i> Stable under normal conditions</p> <p><i>Conditions to avoid:</i> Not applicable</p> <p><i>Materials to avoid:</i> Oxidising agents</p> <p><i>Dangerous decomposition products:</i> Carbon monoxide (CO), acetaldehyde, acidic gases</p>
11.	<p>Toxicological information</p> <p><i>Toxicological tests:</i> Based on MSDS of base material producer</p> <p><i>Experience with man:</i></p> <p><i>Skin contact:</i> Does not contain any materials which are known to stimulate allergic reactions. Grinding dust may cause irritation to people with sensitive skin.</p> <p><i>Eye contact:</i> Dust may cause irritation.</p> <p><i>Inhalation:</i> Dust may cause irritation of respiration tract.</p> <p><i>Ingestion:</i> Low toxicity, LD50 > 2000mg/kg</p>
12.	<p>Ecological information</p> <p><i>Ecotoxicity:</i> Not determined</p> <p><i>Mobility:</i> Not soluble in water, therefore effects on groundwater are unlikely</p> <p><i>Persistence and degradability:</i> Biologically not degradable</p>
13.	<p>Disposal considerations</p> <p>Subject to legislation by local authorities, the product can be disposed of together with domestic refuse and industrial waste. Waste and residues can be incinerated in a plant equipped with flue gas washing, together with domestic waste.</p>
14.	<p>Transport information</p> <p>Railroad RID No restriction.</p> <p>Road ADR No restriction.</p> <p>Sea IMDG Code No restriction.</p> <p>Air ICAO-TI/IATA-DGR No restriction.</p> <p>UN-Classification Not required.</p>

Material Safety data sheet for AIREX® T90 T92

According to Regulation (EC) No. 1907/2006

Page 3 of 3

revised: 25.01.2011

15. Regulatory information

AIREX® T90/T92 rigid plastic foam does not require marking under the dangerous substances and preparation directives 67/548/EWG and 1999/45/EG.

16. Other information

This issue of the safety data sheet replaces the issue released on 23.11.2010.

The information given in this material safety data sheet is accurate to the best of our knowledge, but without any guarantee. It is given in good faith based on the current state of knowledge and experience. It is issued in respect of safety requirements and does not purpose to provide information on the quality of the material.